

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: MANNOL 9954 Super Benzin Oktane Plus
- **UFI:** 1KJV-J02J-800X-XYD2
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Additive
- 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: UAB "SCT Lubricants" Silutes PI. 119 LIT-95112 KLAIPEDA LITHUANIA renata@sct.lt
- Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111
 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

GHS08	health hazard		
STOT RE 1	H372 Causes damage to the central nervous system through prolonged or repeated exposure.		
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.		
GHS05	corrosion		
Eye Dam. 1	H318 Causes serious eye damage.		
GHS07			
Skin Irrit. 2	H315 Causes skin irritation.		
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.		
 • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. 			
	(Contd. on page 2)		



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 1) Hazard pictograms GHS05 GHS08 · Signal word Danger · Hazard-determining components of labelling: Naphtha (petroleum), hydrodesulfurized heavy butan-1-ol · Hazard statements H315 Causes skin irritation. H318 Causes serious eye damage. H372 Causes damage to the central nervous system through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children. P102 P103 Read carefully and follow all instructions. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P273 Avoid release to the environment. Wear eve protection / face protection. P280 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. P362+P364 If skin irritation occurs: Get medical advice/attention. P332+P313 Store locked up. P405 P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 12.05.2023

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

	(Cont	d. of page 2
 Dangerous compor 	nents:	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	65–69%
EINECS: 265-185-4	STOT RE 1, H372; Asp. Tox. 1, H304	
CAS: 71-36-3	butan-1-ol	10–15%
EINECS: 200-751-6	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 104-76-7	2-Ethylhexanol	10–15%
EINECS: 203-234-3	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 128-37-0	Butylated hydroxytoluene	0.1–1%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute 10X. 4, H302	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2. Do not use water.

Foam

Fire-extinguishing powder

- Sand
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

IF



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Particular danger of slipping on leaked/spilled product. Wear protective clothing. 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. · 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

71-36-3 butan-1-ol (15.0%)

OEL Long-term value: 20 ppm

(Contd. on page 5)



Printing date 12.05.2023

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 4)

104-76-7 2-Ethylhexanol (15.0%)

OEL Long-term value: 5.4 mg/m³, 1 ppm

IOELV

12108-13-3 tricarbonyl(methylcyclopentadienyl)manganese (7.0%)

OEL Long-term value: 0.2 mg/m³

Sk

128-37-0 Butylated hydroxytoluene (1.0%)

OEL Long-term value: 2 mg/m³

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 5)

IE

[.] 9.1 Information on basic physical and chemical	properties
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Undetermined.
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
Flash point:	35 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health	
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	20–30 %
· VOC (EC)	20–30 %
Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard	
classes	
·Explosives	Void
· Flammable gases	Void
Aerosols	Void
	Void
· Aerosols · Oxidising gases · Gases under pressure	Void Void



Printing date 12.05.2023

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

		(Contd. of page 6)
· Flammable solids	Void	
 Self-reactive substances and mixtures 	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acu	te Toxicity	y Estimates)
Oral	LD50	4,972–7,830 mg/kg
Dermal	LD50	13,133–19,700 mg/kg
Inhalative	LC50/4 h	73.3–110 mg/l
71-36-3 b	utan-1-ol	
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)
104-76-7	2-Ethylhe>	canol
Oral	LD50	2,049 mg/kg (rat)
Dermal	LD50	1,970 mg/kg (rabbit)
	•	(Contd. on page 8)



Printing date 12.05.2023

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 7)

128-37-0 Butylated hydroxytoluene

Oral LD50 890 mg/kg (rat)

· Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- Causes damage to the central nervous system through prolonged or repeated exposure.
- Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Euro	pean waste catalogue
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
	(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

(Contd. of page 8)

Trade name: MANNOL 9954 Super Benzin Oktane Plus

HP6 Acute Toxicity

HP14 Ecotoxic

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA not regulated · 14.2 UN proper shipping name · ADR, IMDG, IATA not regulated 14.3 Transport hazard class(es) · ADR, IMDG · Class not regulated ·IATA · Class not regulated · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: • Marine pollutant: Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Not applicable. · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · UN "Model Regulation": not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 10)

- IE



Printing date 12.05.2023

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

(Contd. of page 9)

Seveso category

 H2 ACUTE TOXIC
 P5c FLAMMABLE LIQUIDS

 REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
 None of the ingredients is listed.
 REGULATION (EU) 2019/1148
 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of

licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS: Product safety department.
- · Contact: Mrs. Zubaite
- Date of previous version: 21.09.2022
- Version number of previous version: 2209
- Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

IE



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2209)

Revision: 20.01.2023

Trade name: MANNOL 9954 Super Benzin Oktane Plus

Aquatic Advance in Advance of the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • * Data compared to the previous version altered.	IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1	(Contd. of page 10)
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1	
	Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	